AL45 Roller Shutter

45mm Aluminium Roller Shutter

ULTRA STRONG

The AL45 Roller Shutters are ideal for both external and internal installations in most building projects, including counter tops, trucks, over windows, display cabinets, warehouses, factories, recreation and sporting centres, mining and heavy industry workshop facilities.

The maximum size is 3m high x 3m wide. The Roller Shutters can be installed with removable mullions for larger opening widths.

REQUEST A QUOTE

ANVIL
ASSA ABLOY

Anvil Industrial Doors
85 Christable Way, Landsdale,
Western Australia, 6065
PO Box 1767, Wangara WA 6947
Phone: (08) 9302 3355
Fax: (08) 9302 3399

Specifications

CURTAIN SLAT

Anodized aluminum extruded hollow section profile (.394kg per metre) with a face depth of 45mm which displays the same visual look on both sides.

Nylon clips are fitted to every second slat to prevent lateral movement and provide smooth operation. Optional bottom rail locking via mortice key lock centrally mount into slat, not available on motorised doors.

Finishings available in most powder coat colors

GUIDES

Anodized aluminum channel section profile 70mm wide(1.423kg per metre) with hollow back section 22mm in depth designed to withstand force from intrusions and high wind loadings.

Hollow back allow for concealed fixings.

Nylofelt fitted to both internal faces of guides for quiet and smooth operation.

AXLE ASSEMBLY

60mm aluminum octagonal axle suits compact spring assembles and internal tube motor drive systems. Motorised doors can be powered DC or AC 240v and operated by wired key switch or wireless remote.

BOX COVER ENCLOSURES

Covers and protects door bundle and working from external and internal surroundings. Aluminum die cast side plates locating to top of guide ends and anchoring motor or spring mounts. Box and cover sizing will vary depending on door height. Finishings available in most powder coat colours.

FINISH

Natural anodized or full range of powder coat colours.

ANVIL

ASSA ABLOY

NOTES