

**REQUEST A QUOTE**

Anvil Industrial Doors  
85 Christable Way, Landsdale,  
Western Australia, 6065  
PO Box 1767, Wangara WA 6947  
Phone: (08) 9302 3355  
Fax: (08) 9302 3399

Perforated  
Roller Shutters

## Perforated Roller Shutter

BHP Galvabond G2 Z275 steel in 1.0mm gauge slats.

### SOUND AND SECURE

Roller Shutters are a proven versatile style of door, ideal for non-cyclonic areas. They are available with smooth manual or power operation in the full colour range of powder coated finishes. They can be sized to suit openings up to a large 36m<sup>2</sup>.

Roller shutters are ideal for both external and internal installations in most building projects including warehouses, factories, shopping centres, recreation and sporting centres, mining and heavy industry workshop facilities.





## Specifications

### DOOR CURTAIN ASSEMBLY

105mm slat profile (Galvabond- 1.0mm or 1.2mm-G2-Z275) with Windlocked Nylon clip which secures curtain into guides.

### HEAVY DUTY GUIDE ASSEMBLY

90mm deep with wall thickness of 2.95mm and formed lock rail running full length of guide to secure wind lock clips.

### DRUM ASSEMBLY

The drum is manufactured from mild steel tube. The drum houses bearings counter balancing helical torsion springs, capable of producing sufficient torque to ensure ease of operation of the curtain from any position. With 1.0mm or 1.2mm steel slats with cast windlock clips every slat. Optional powder coat colours. AS/NZS 1170.2 - 2002. With patent pending (AU2012261562) Cyclonic guide clamps

All torsion spring used are coiled and heat treated to AS for performance and durability.



All drum and axle components are fabricated using high quality carbon steel.

### BOTTOM RAIL ASSEMBLY

Aluminium T/Bar with bottom weather seal.

### MOTOR OR MANUAL

Motor operation is a 1hp, 3 phase, Grifco operator









## NOTES

A series of horizontal dotted lines for writing notes.